



S-SOLENOID  
 FI-FLOW INDICATOR  
 BV-BALL VALVE  
 GV-GLOBE VALVE  
 TE- THERMOCOUPLE  
 TI- TEMPERATURE INDICATOR  
 TS- TEMPERATURE SWITCH  
 I INTERLOCKS  
 M1,M2, S1,S2,S3,S4,S5  
 E-STOP, FEEDER, GRIT SCREEN

REV. NO	DATE	BY	APPV.	DESCRIPTION

**TOLERANCES UNLESS OTHERWISE NOTED**

WHOLE NUMBER DIM.	1/16"	ANGULAR DIM.	1/2-
FRACTIONAL DIM.	1/16"	DECIMAL DIM. (.XX)	.010
		DECIMAL DIM. (.XXX)	.005

**NOTICE:** THE INFORMATION CONTAINED HEREIN IS PROPRIETARY TO LOUISVILLE DRYING MACHINERY AND SHALL NOT BE REPRODUCED OR DISCLOSED IN WHOLE OR IN PART, NOR USED FOR ANY DESIGN OR MANUFACTURING PURPOSE UNLESS AUTHORIZED IN WRITING BY LOUISVILLE DRYING MACHINERY



CUSTOMER: \_\_\_\_\_  
 DESCRIPTION: SLAKER CONTROLS


 12711 TOWNPARK WAY  
 LOUISVILLE, KY 40219-1804 USA  
 TELEPHONE (502) 969-3535  
 FAX (502) 969-9028

DWG. BY: NEG	DATE: 12-20-2009
CHK. BY: -	
APPROVED BY: -	
SCALE:	DWG.# DV-5030013
	SHT. # OF:

NEXT DWG'S: